



## 2MP Sound-Light Alarm IR

- Sound-Light Alarm Bullet Smart IR
- 1/2.8"SONY Starvis Back-illuminated CMOS Sensor
- H.265+/H.265/H.264+/H.264
- Compression Method
- 3MP Fixed Lens 6mm
- Support White light LED
- With Internal POE and SD Card Slot



### SPECIFICATION

<b>Model NO.</b>	<b>N6010L</b>
<b>Camera</b>	
Image Sensor	1/2.8" SONY Starvis Back-illuminated CMOS Sensor
Resolution	2MP 1080P
Effective Pixels	1945(H)*1097(V)
Compression	H.264/H.264+/H.265/H.265+/JPEG/AVI /MJPEG
TV System	PAL/NTSC
Electronic Shutter Time	Auto: PAL 1/25-1/10000Sec; NTSC 1/25-1/10000Sec
Minimum Illumination	0.001Lux
S/N Ratio	≥52dB
Scanning System	Progressive
Video Output	Network
Reset Button	Internal
<b>Lens</b>	
Focus Length	Board Lens 6mm/F1.2
Focus Control	Fixed
Lens Type	Fixed
Pixels	3MP
<b>Night Vision</b>	
Infrared LED	No, Support Whilit light LED 45μ x 4PCS
Infrared Distance	/
IR Status	/
IR Power On	smart, manual & time mode
<b>Network</b>	
Ethernet	RJ-45 (10/100Base-T)
Wireless	3dbi ,Dual Antena Wi-Fi(IEEE802.11b/g/n/a/c) 2.4Ghz,5Ghz Range: No obstacles 300m Max
Protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP
ONVIF	Support ONVIF 2.4
P2P	YES, Support QR Code
POE	/
Video Delay	0.3S (Within the Lan)
Main Stream 1	2048*1536@15fps
Main Stream 2	1920*1080@30fps
Main Stream 3	1280*720@30fps
Sub Stream 1	720*480@15fps 720*480@30fps
Sub Stream 2	/
Sub Stream 3	/
Tri Stream	352*288@15fps 352*288@30fps
IE Brower	IE8-11, Google Chrome (lower than Ver44), Firefox (lower than Ver53), Mac Safari
Smart Phone	iPhone, iPad, Android, Android Pad
<b>Camera Features</b>	
Day/Night	Color
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, FLK(Flicker Control), Video Tampering
Starlight	YES
Corridor Pattern	/
Defog Mode	Support
ROI	Support
BLC	Support
HDR	/
WDR	Support
Motion Detection	Support
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian,Nederlands
<b>Interface</b>	
Audio	Bulit in Audio in/Buzzer out
Alarm	Yes, I/O Alarm 1 in /1 out
SD Card Slot	Yes, Support Max 128GB
Video	Yes, BNC output
<b>General</b>	
Housing	Metal ,IP67
Anti-cut Bracket	Optional
IR Cut Filter	YES
Operation Temperature	-20℃ ~ +60℃ RH95% Max
Storage Temperature	-20℃ ~ +60℃ RH95% Max
Power Source	DC12V±10%, 1150mA
Dimension	220(W) x 105(H) x 109(D)mm
Weight	1650g